

L20: NBS DOORSET SPECIFICATION

Novista Riser

410A Concealed Riser Single NFR / FD30 / FD60 and 41dB.

- Drawing reference(s): Refer to plans, door types and Door Schedule.
- Manufacturer and reference: Aspex Doorsets, Novista Riser Steel.
- Security Requirements: None
- Fire performance: FD120
Smoke control: Required.
- Acoustic performance: 41dB
- Door leaf:
Steel with insulated core
Thickness: 48mm
Facings: Primed, RAL 9010, Any RAL colour
- Frame and architraves:
Frame: Novista
Material: Galvanised Steel
Architraves: Not required.
- Ironmongery:
Hinges: Pivot.
Locks: Square key multipoint deadlock, Europrofile multipoint deadlock
Fire seals: Intumescent seal arrangements in line with Aspex tested evidence supplied and fitted into the door.

410B Concealed Riser Double NFR / FD30 / FD60 and 41dB.

- Drawing reference(s): Refer to plans, door types and Door Schedule.
- Manufacturer and reference: Aspex Doorsets, Novista Riser Steel.
- Security Requirements: None
- Fire performance: FD120
Smoke control: Required.
- Acoustic performance: 41dB.
- Door leaf:
Core: Steel with insulated core.
Thickness: 48mm
Facings: Primed, RAL 9010, Any RAL colour
- Meeting Stiles: Square
- Frame and architraves:
Frame: Novista
Material: Galvanised Steel
Architraves: Not required.
- Ironmongery:
Hinges: Pivot
Locks: Square key multipoint deadlock, Europrofile multipoint deadlock
Factory fitted flush bolts to inactive leaf.
Fire seals: Intumescent seal arrangements in line with Aspex tested evidence supplied and fitted into the door.