

## PAS24 Access Control – Communal Door

Not to scale



PUSH SIDE



PULL SIDE



### Specification

This door is manufactured with a solid core and has hardwood lipping's to all 4 sides.

- PAS24 tested from both directions
- Access control compatibility with various systems
- High density chipboard core
- 8mm hardwood lipping's on all 4 sides
- Overall thickness 54mm for NFR, FD30 and FD60
- Up to 35dB acoustic rated (with the correct seal arrangement)
- Tested to DD171 and classed as severe duty
- Choice of vision panel design options available

### Ironmongery details

- High-security nightlatch
- High-security cylinder & turn override option
- High-security electric strike changeable on-site between fail safe/fail secure
- Lever handle or pull handle options
- Kick plate & fire signage

### Door leaf/set Finishes

- Primed
- Veneered
- Laminated
- Factory-painted

### Performance

- Fire tested to BS 476 part 22
- All fire rated doorsets manufactured under the stringent BWF Certifire scheme
- Doorsets meet requirements of Approved Document M for clear opening widths

### Suitable for...

- ✓ PAS24 Access Control Bin store, Refuse Room
- ✓ PAS24 Access Control Communal/ Circulation/ Stair etc.

### FSC Certified

Sustainably sourced & carefully produced to design specification

### Packaging

Protective packaging and delivered fully assembled in palletised form (varies per order)

