

PAS24 Entrance Doorset

Not to scale





CGI/ PULL SIDE

Specification

All fire doors are purpose-made to sizes required, extensive size ranges are validated by an independent test or authoritative assessment

- Tested to PAS24: 2016
- Door leaf constructed from a severe duty core tested to DD171, with hardwood lipping's on all 4 sides
- Structural opening size of up to 2400mm high and 1050mm wide
- Fire rating FD30S (44mm) and FD60S (54mm)
- Acoustic rating 29dB, 32dB and 35dB options
- Smoke/ Air tested compression smoke seals tested in accordance with BS - 9999:2017

Ironmongery details

- High-security key or electronic locking options available all tested to PAS24
- Wide variety of lever handle options
- Concealed or surface mounted door closers
- Security letter box & door viewer are optional
- Choice of ironmongery finishes stainless steel, black, brass, bronze and copper, PVD etc

Door leaf/set finishes

Primed, Factory painted, Veneer, Stained, Laminated. All available in design options flush, grooved or panelled

Performance

- Fire tested to BS 476 part 22
- All fire rated doorsets manufactured under the stringent BWF Certifire scheme
- Doorsets meet requirements of Approved Document M for clear opening widths

Configuration

- DT03 PAS24 Entrance Door (Single)
- DT08 PAS24 Electric Strike (Single)

Suitable for...

- PAS24 Entrance Apartment Doorsets
- ✓ PAS24 Entrance Commercial Doorsets

Packaging

Protective packaging and delivered in palletised form (varies per order)







